

**SPECIFICATIONS**  
**SOUND LEVEL METER 2013:**

Standards	: Designed as per IS:9779- 1981, Type 2
Measuring Range	: 50-114 dB(A)
Microphone	: 1/2" Electret Condenser non-detachable
Calibration	: Factory calibrated, Field calibration by Acoustic calibrator 3022. Calibration traceable to NPL.
Detector	: True RMS
Resolution	: 0.1 dB
Display	: LCD 3 1/2 digit
Error Indicators	: Overload and under range indication
Frequency weighting	: A weighted as per IS:9779- 1981.
Time Weighting	: Slow or Fast as per IS: 9779- 1981.
Battery	: 4 nos AA sized Alkaline cells, user replaceable
Battery Indicator	: Lo Bat shows on the display when battery is low
Construction	: Rugged die cast, reflection free, aluminium enclosure
Temperature	: 0 to 50 degree Celsius
Humidity	: 0 to 90% none condensing
Dimensions (mm)	: 78mm (W) x 26mm (H) x 275mm (L)
Weight	: 500 gms approx.
Standard accessories	: Synthetic-leather carrying case, Windshield, Operation Manual, Initial set of 4 AA Batteries, Calibration Certificate traceable to NPL with 1 year validity.

Marketed by **ABE** (Accurate Balancing Equipment)

5 UK Indl. Est. Behind Durian Furniture, opp Oswal park,  
Pokharan, Road no.2, Thane (W) 400 602 Maharashtra, India,  
Tel:- 022- 21737777 / 78 / 79 Telefax:- 022- 21737788

Email :- admin@accuratebalancing.com / sales@accuratebalancing.com / contact@accuratebalancing.com